

Overview

The **ECB-400 Series** are microprocessor-based programmable controllers designed to control various building automation applications such as air handling units, multi-zone applications, chillers, boilers, pumps, cooling towers, and roof top units. The ECB-400 Series can also be used for lighting control applications. This controller uses the BACnet[®] MS/TP LAN communication protocol and is BTL[®]-Listed as BACnet Advanced Application Controllers (B-AAC).

This series contains six models: ECB-400, ECB-403, ECB-410, ECB-413, ECB-450, and ECB-453. These models have universal inputs and outputs that are ideal for controlling a wide range of HVAC equipment. The ECB-450 and ECB-453 models have a full-color backlit-display and a jog dial for turn and select navigation to access a wide range of internal controller functions: View, edit, and override values, tune PID loops with system response graphing, view schedule status, and acknowledge alarms.

These controllers work with a wide range of sensors, such as those in the Allure™ EC-Smart-Vue series of communicating room sensors that feature a backlit-display and graphical menus. These sensors are used for indoor temperature measurement, setpoint adjustment, fan speed selection, and occupancy state override. In addition, these controllers are Open-to-Wireless™ ready, and when paired with the Wireless Receiver, they work with a variety of wireless battery-less sensors and switches.

Custom program these controllers using EC-gfxProgram through EC-Net^{AX} Pro which is powered by the Niagara^{AX} Framework[®]. This allows you to quickly and easily create your own control sequences capable of meeting the most demanding requirements of any engineering specification.

Applications

- Meets the requirements of the following applications:
 - Air Handling Units
 - Multi-Zone Applications
 - Chillers
 - Boilers
 - Cooling Towers
 - Roof Top Units
- Improves energy efficiency when combined with:
 - CO₂ sensors as part of a demand-controlled ventilation strategy that adjusts the amount of fresh air intake according to the number of building occupants
 - Variable-frequency drives to adjust motor speed according to the instantaneous demand of the application
- Works with a wide range of wireless battery-less sensors

Features & Benefits

- Use the EC-gfxProgram's state-of-the-art visual programming wizard to customize controller operation to meet specific engineering requirements. EC-gfxProgram is accessible through EC-Net^{AX} Pro which is powered by the Niagara^{AX} Framework -based management platform.
- Accelerate custom programming development by using pre-built HVAC control sequences supplied with EC-gfxProgram.
- Available with an optional Wireless Receiver that supports up to 28 wireless inputs, letting you create wire-free installations and use various wireless battery-less sensors and switches.
- BTL B-AAC-listed, guaranteeing interoperability with other manufacturers' BTL listed controllers.
- With 12 software configurable universal inputs and 12 software configurable outputs, this controller series covers all medium to large-size industry-standard HVAC applications. Four of these inputs also support fast pulse count reading up to 50 Hz frequency for gas, water, and electric meters.
- 0-20mA inputs and outputs use an internal jumper that eliminates the need for external resistors.
- Highly accurate universal inputs support thermistors and resistance temperature detectors (RTDs) that range from 0 Ohms to 350 000 Ohms, giving you the freedom of using your preferred or engineer-specified sensors, in addition to any existing ones.
- Supervised HOA switches and potentiometers, allowing you to override control actions for testing purposes or when performing equipment maintenance.
- Rugged hardware Inputs and Outputs eliminate need for external protection components, such as diodes for 12V DC relays.

ECB-400 Series Controllers



Model	ECB-400	ECB-403	ECB-410	ECB-413	ECB-450	ECB-453
Points	24-Point Controller	24-Point Controller	24-Point Controller with HOA	24-Point Controller with HOA	24-Point Controller with Color Display	24-Point Controller with Color Display
Universal hardware inputs	12 ¹	12 ¹	12 ¹	12 ¹	12 ¹	12 ¹
Allure EC-Smart-Vue ²	12	12	12	12	12	12
Wireless inputs ³	28	28	28	28	28	28
15 Vdc Power Supply	■	■	■	■	■	■
Digital (triac) outputs		8		8		8
Universal outputs	12	4	12	4	12	4
HOA switch & potentiometer			■	■		
Operator interface: Interactive color display to monitor and override controller parameters					■	■
Product Number	CDIB-400X-00	CDIB-403X-00	CDIB-410X-00	CDIB-413X-00	CDIB-450X-00	CDIB-453X-00

1. The first four inputs are software configurable for pulse counting up to 50 Hz and are compatible with an S0 rated (optically-isolated) output.
2. A controller can support a maximum of two Allure EC-Smart-Vue models equipped with a CO₂ sensor. The remaining connected Allure EC-Smart-Vue models must be without a CO₂ sensor.
3. All controllers are Open-to-Wireless ready. Available when an optional Wireless Receiver is connected to the controller. Some wireless sensors may use more than one wireless input from the controller.

Recommended Applications


Model	ECB-400	ECB-403	ECB-410	ECB-413	ECB-450	ECB-453
Roof Top		■		■		
Air Handling Unit	■	■	■	■	■	■
Multi-zone Application	■		■		■	■
Chiller	■	■	■	■	■	■
Boiler	■	■	■	■	■	■
Cooling Tower	■	■	■	■	■	■

BACnet Objects List

Model	ECB-400	ECB-403	ECB-410	ECB-413	ECB-450	ECB-453
BACnet Calendar Objects	2	2	2	2	2	2
BACnet Schedule Objects	10	10	10	10	10	10
BACnet PID Loop Objects	30	30	30	30	30	30
BACnet Input Objects (AI, BI, MSI) ¹	64 ²					
BACnet Output Objects (AO, BO) ¹	12 ³	4 ³	12 ³	4 ³	12 ³	4 ³
BACnet BV Objects						
- Commandable ¹	20	20	20	20	20	20
- Non-Commandable	55	55	55	55	55	55
BACnet MSV Objects						
- Commandable ¹	20	20	20	20	20	20
- Non-Commandable	55	55	55	55	55	55
BACnet AV Objects						
- Commandable ¹	35	35	35	35	35	35
- Non-Commandable	115	115	115	115	115	115
BACnet Alarm Notification Classes	5	5	5	5	5	5

1. Supports object internally-generated alarms (intrinsic reporting) which are dynamically instantiated upon object creation.
2. This consists of Hardware Inputs, Allure EC-Smart-Vue inputs, and Open-To-Wireless inputs.
3. This consists of Hardware Outputs.

Additional Features & Benefits for the ECB-410, ECB-413, ECB-450, and ECB-453 Models



The ECB-410 and ECB-413 have supervised Hand-Off-Auto (HOA) switches and potentiometers provide feedback to the software of an operator's manual override of an output. HOA switches are ideal for testing purposes or when performing equipment commissioning and maintenance.



The ECB-450 and ECB-453 have a large color backlit-display that allows an operator to have immediate access to internal controller data.

- View, edit, and override values. The status is color coded to show if the value is in alarm or overridden.
- Visually tune PID loops with system response graphing.
- View active alarm list including details and acknowledge alarms.
- View schedule status.
- Create a list of favorites to provide quick access to commonly-used values.
- Multi-User access management.
- Multilingual interface: English, French, German, etc.

Open-to-Wireless Series – Controller Wireless Receiver Add-on



To reduce the cost of installation, and minimize the impact on existing partition walls, the Wireless Receiver enables these controllers to communicate with a line of wireless battery-less room sensors and switches. These Wireless Receivers are available in EnOcean 315MHz and 868.3MHz versions.

Note that controllers have one wireless port to support a single Wireless Receiver.

For more information about the EnOcean and Open-to-Wireless technologies, refer to the [Open-to-Wireless Solution Guide](#). For more information about the Wireless Receiver module, refer to the [Wireless Receiver Datasheet](#). These documents can be found on our web site.

Supported Platforms




EC-Net^{AX} Solution

The EC-Net^{AX} multi-protocol integration solution is web-enabled and powered by the Niagara^{AX} Framework, establishing a fully Internet-enabled, distributed architecture for real-time access, automation and control of devices. The EC-Net^{AX} open framework solution creates a common development and management environment for integration of LONWORKS®, BACnet® and other protocols. Regardless of manufacturer and protocol, the EC-Net^{AX} system provides a unified modeling of diverse systems and data, providing one common platform for development, management and enterprise applications.

EC-Net^{AX} Wizards


EC-gfxProgram Graphical Programming Interface (GPI)



Distech Controls' EC-gfxProgram is a programming tool that allows you to quickly create control sequences by "dragging and dropping" block objects and then linking the objects with a simple "click, select and release". Select objects from an extensive library of over 100 commonly used functions as well as create your own custom blocks. With a user-friendly interface and intuitive programming environment, HVAC programming could not be easier. Refer to the EC-gfxProgram datasheet for more information.

- Program both ECP and ECL Series LONWORKS and ECB Series BACnet controllers with the same tool.
- Supplied as freeware – there are no associated licensing costs.
- Live debugging allows user to view code execution, input/output values and to detect errors in real-time.
- A code library for managing your favorite or most commonly used code or code sections.

EC-Net^{AX} Scheduling / EC-gfxProgram EC-Schedule



Configure the controller's built-in schedules and holidays from the EC-Net^{AX} solution (ECB and ECL series controllers), or directly from within EC-gfxProgram (ECB and ECL series controllers) with an easy-to-use point, drag, and click interface. It features a weekly schedule for regular, repeating, events by "time-of-day" and "day-of-week", while a holiday schedule is available to define events for specific days.

- Easily configure schedules using a graphical slider.
- Allows you to easily copy and paste entries. Duplicate a schedule entry for Monday to Friday.
- Special events allow you to set exceptions such as holidays to a schedule.
- Holidays can be set for recurring events such as the 9th day, or the 3rd Thursday of a given month.
- A schedule has an effective period during which it is active.
- Schedule provides Next State and Time to Next State that are ideal for use with programming functions such as Optimum Start or Morning Warm Up.

Complementary Products

Temperature Sensors

Allure™ EC-Smart-Vue Series



Line of communicating room temperature sensors with communication jack, a backlit-display and configurable graphic menus that allow occupants to set occupancy, setpoint adjustment, fan speed, or any other system parameters. Models are available with any combination of the following options: Humidity sensor, motion sensor, and CO₂ sensor. The ECO-Vue™ icon () shows how environmentally-friendly the zone's energy consumption is in real time.

Allure EC-Sensor Series



Line of discrete temperature sensors. Models are available with the following options: Communication jack, occupancy override button, setpoint adjustment, and fan speed selection.

Open-to-Wireless Sensors and Switches

Allure Wireless Battery-less ECW-Sensor Series



Line of wireless, battery-less room temperature sensors. Models are available with the following options: Occupancy override button, setpoint adjustment, and fan speed selection.

These sensors are available in EnOcean 315MHz and 868.3MHz versions. The controller must be equipped with a [Wireless Receiver](#).

Wireless Sensors and Switches



A wide range of self-powered wireless sensors and switches, including the following: Motion detector and light sensor, 2-/4-channel wireless light switches (North American and European models), outdoor temperature sensor, surface temperature contact sensor, duct temperature sensor, and more.

These sensors are available in EnOcean 315MHz and 868.3MHz versions. The controller must be equipped with a [Wireless Receiver](#).

For more information about the available wireless sensors and switches, refer to the [Open-to-Wireless Solution Guide](#) which can be found on our web site.


Relay and Relay Base



A SPDT (NO/NC) dry contact relay with a 12VDC coil. This relay's low-power coil allows a controller's universal output to control high-power loads. Optional hardware available includes a din-rail mountable socket base and a red LED for relay status indication.

For more information on these or other Distech Controls products, refer to our web site.

Controller Dimensions



Product Specifications

Power

Voltage	24VAC/DC; $\pm 15\%$; 50/60Hz; Class 2
Protection	3.0A user-replaceable fuse
Power Consumption	
- ECB-400/ECB-410	22 VA typical plus all external loads ¹ , 60 VA max.
- ECB-403/ECB-413	22 VA typical plus all external loads ¹ , 50 VA max.
- ECB-450	25 VA typical plus all external loads ¹ , 63 VA max.
- ECB-453	25 VA typical plus all external loads ¹ , 53 VA max.

Interoperability

Communication Bus	BACnet MS/TP
BACnet Profile	B-AAC ²
EOL Resistor	Built-in, jumper selectable
Baud Rates	9600, 19 200, 38 400, or 76 800 bps
Addressing	Dip Switch

Hardware

Processor	STM32 (ARM Cortex™ M3) MCU, 32 bit
CPU Speed	72 MHz
Real Time Clock (RTC)	Built-in Real Time Clock with rechargeable battery Network time synchronization is initially required
RTC Battery	20 hours charge time, 20 days discharge time Up to 500 charge / discharge cycles
Memory	1 MB Non-volatile Flash (applications) 2 MB Non-volatile Flash (storage) 96 kB RAM
Status Indicator	Green LEDs: Power Status & LAN Tx Orange LEDs: Controller Status & LAN Rx
Communication Jack	BACnet 1/8" (3.5mm) stereo audio jack

Environmental

Operating Temperature	0°C to 50°C; 32°F to 122°F
Storage Temperature	-20°C to 50°C; -4°F to 122°F
Relative Humidity	0 to 90% Non-condensing

Enclosure

Material	FR/ABS
Color	Black & blue casing & grey connectors
Dimensions	

- ECB-400/ECB-403/ ECB-410/ECB-413	7.7 L x 4.7 W x 2.03" H (195.58 x 119.38 x 51.47mm)
- ECB-450/ECB-453	7.7 L x 4.7 W x 2.55" H (195.58 x 119.38 x 64.68mm)

Shipping Weight

- ECB-400/ECB-403/ ECB-410/ECB-413	1.17lbs (0.53kg)
- ECB-450/ECB-453	1.28lbs (0.58kg)

Inputs

Input Types	Universal; software configurable
-Voltage	- 0 to 10VDC (40k Ω input impedance) - 0 to 5VDC (high input impedance)
-Current	0 to 20mA with 249 Ω jumper configurable internal resistor
-Digital	Dry contact
-Pulse	UI1 to UI4; 50Hz maximum; Min 10ms On/10ms Off - SO output compatible UI5 to UI12: 1Hz maximum; Min 500ms On/500ms Off - Dry contact
-Resistor	0 to 350 K Ω . All thermistor types that operate in this range are supported. The following temperature sensors are pre-configured:
<i>Thermistor</i>	10K Ω Type 2, 3 (10K Ω @ 25°C; 77°F)
<i>Platinum</i>	PT1000 (1K Ω @ 0°C; 32°F)
<i>Nickel</i>	RTD Ni1000 (1K Ω @ 0°C; 32°F) RTD Ni1000 (1K Ω @ 21°C; 69.8°F)
Input Resolution	16-bit analog / digital converter
Power Supply Output	15VDC; maximum 240mA (12 inputs x 20mA each)

Outputs

Digital	24VAC Triac, digital (on/off), floating, or PWM; software configurable - 0.5A continuous - 1A @ 15% duty cycle for a 10-minute period - PWM control: adjustable period from 2 to 65sec. - Floating control: - Min pulse on/off: 500msec. - Adjustable drive time period
Universal	External power supply 0-10VDC linear, digital 0-12VDC (on/off), floating PWM, or 0-20mA (jumper configurable); software configurable. Built-in snubbing diode to protect against back-EMF, for example when used with a 12VDC relay. - PWM control: adjustable period from 2 to 65sec. - Floating control: - Min pulse on/off: 500msec. - Adjustable drive time period - HOA: Hand-Off-Auto switch (when equipped) - Hand position potentiometer range: 0-12.5VDC - 60mA max. @ 12VDC (60°C; 140°F)
Load Resistance	- Minimum 200 Ω for 0-10VDC and 0-12VDC outputs - Maximum 500 Ω for 0-20mA output
Auto-reset Fuse	- 60mA @ 60°C; 140°F - 100mA @ 20°C; 68°F
Output Resolution	10-bit digital / analog converter

Product Specifications (continued)

Wireless Receiver³

Communication	EnOcean wireless standard
Number of wireless inputs ⁴	28
Supported Wireless Receivers	Wireless Receiver (315)
Receivers	Wireless Receiver (868)
Cable	Telephone cord
- Connector	4P4C modular jack
- Length (maximum)	6.5ft; 2m

Standards and Regulation

CE -Emission	EN61000-6-3: 2007; Generic standards for residential, commercial and light-industrial environments
-Immunity	EN61000-6-1: 2007; Generic standards for residential, commercial and light-industrial environments
FCC	This device complies with FCC rules part 15, subpart B, class B



UL Listed (CDN & US)	UL916 Energy management equipment
Material ⁵	Plastic housing, UL94-5VB flammability rating Plenum rating per UL1995



CEC Appliance Database Appliance Efficiency Program⁶

1. External loads must include the power consumption of any connected modules such as an Allure EC-Smart-Vue sensor. Refer to the respective module's datasheet for related power consumption information.
2. Refer to Distech Controls' Protocol Implementation Conformity Statement for BACnet.
3. Available when an optional external Wireless Receiver module is connected to the controller. Refer to the Open-to-Wireless Solution Guide for a list of supported EnOcean wireless modules.
4. Some wireless modules may use more than one wireless input from the controller.
5. All materials and manufacturing processes comply with the RoHS directive  and are marked according to the Waste Electrical and Electronic Equipment (WEEE) directive .
6. California Energy Commission's Appliance Efficiency Program: The manufacturer has certified this product to the California Energy Commission in accordance with California law.

ECB-450 & ECB-453 Display

Display Type	Backlit-color LCD
Display Resolution	400 W × 240 H pixels (WQVGA)
Effective Viewing Area	2.4 L × 1.4" H (61.2 × 36.7mm) 2.8" (71mm) diagonal
Menu Navigation	Jog dial turn and select navigation with Exit button

Allure EC-Smart-Vue Sensor

Communication	RS-485
Number of sensors per controller	Up to 12, in daisy-chain configuration
Cable	Cat 5e, 8 conductor twisted pair
Connector	RJ-45

Communication Protocols



Total Quality Commitment

All Distech Controls product lines are built to meet rigorous quality standards. Distech Controls is an ISO 9001 registered company.

©, Distech Controls Inc., 2010. All rights reserved. Specifications subject to change without notice.

Images are simulated. Distech Controls, the Distech Controls logo, Open-to-Wireless, Innovative Solutions for Greener Buildings, ECO-Vue, and Allure are trademarks of Distech Controls Inc.; LONWORKS is a registered trademark of Echelon Corporation; Niagara^{AX} Framework is a registered trademark of Tridium, Inc.; ARM Cortex is a registered trademark of ARM Limited; BACnet is a registered trademark of ASHRAE; BTL is a registered trademark of the BACnet Manufacturers Association; Windows, Visual Basic.Net are registered trademarks of Microsoft Corporation. EnOcean is a registered trademark of EnOcean GmbH. All other trademarks are property of their respective owners.

