

RCL-PFC-107



RCL-PFC-108



RCL-PFC-207



RCL-PFC-208



General	RCL-PFC-107	RCL-PFC-108	RCL-PFC-207	RCL-PFC-208
Din-Rail Mounting	■	■	■	■
LONMARK® Device Class	SCC - Fan Coil	SCC - Fan Coil	SCC - Fan Coil	SCC - Fan Coil
Inputs				
Configurable Inputs	6	6	6	6
including:				
- Digital Inputs ¹	Up to 4	Up to 4	Up to 4	Up to 4
- Sensor Inputs ¹	Up to 2	Up to 2	Up to 2	Up to 2
- Analog Inputs ¹	Up to 3	Up to 3	Up to 3	Up to 3
1 Depending on input configuration. Please refer to the datasheet for more information				
Outputs				
Electric Heater Outputs	1 x 2 kW	1 x 2 kW	1 x 2 kW	1 x 2 kW
Analog Outputs 0-10 V			2	2
Fan Outputs	3	3	3	3
PWM Valve Outputs 230 V - 10A	2		2	
PWM Valve Outputs 24 V - 300mA		2		2
24 VAC Generation 7 VA				■
Light & sunblinds add-on modules support (up to 4 lighting and 4 sunblinds commands)	■	■	■	■
Power Input				
230 VAC	■	■	■	■

RCL-PFC-107



RCL-PFC-108



RCL-PFC-207



RCL-PFC-208



Configuration

	RCL-PFC-107	RCL-PFC-108	RCL-PFC-207	RCL-PFC-208
EC-Net ^{AX} Wizard & LNS Plug-in	■	■	■	■

Communication

LONMARK Certified	■	■	■	■
-------------------	---	---	---	---

Recommended Applications

2 Pipe Fan Coil	■	■	■	■
2 Pipe Fan Coil with Changeover	■	■	■	■
2 Pipe Fan Coil with Electric Heater	■	■	■	■
2 Pipe Fan Coil with Electric Heater and Changeover (cascade)	■	■	■	■
4 Pipe Fan Coil	■	■	■	■
4 Pipe Fan Coil with Electric Heater	■	■	■	■
Electric Heater	■	■	■	■
Unit Ventilator	■	■	■	■
Chilled Ceiling	■	■	■	■
Variable Fan Speed Control			■	■
0-10 V Valves Control			■	■
Air Quality Management			■	■

RCL-PFC-107



RCL-PFC-108



RCL-PFC-207



RCL-PFC-208



Compatibility

Open-to-Wireless™ ready	■	■	■	■
Allure™ RS Series Analog Room Sensors	■	■	■	■
Allure EC Series Analog Room Sensors	■	■	■	■
Allure RS Series Digital Room Sensors	■	■	■	■
Allure EC Series Digital Room Sensors				
RJ9 Multi-Sensors	■	■	■	■
RJ45 Multi-Sensors				
Max number of Digital Room Devices per controller	1	1	1	1

Controller Naming Conventions:

RCL-PFC-207

7: 230 VAC Valves
8: 24VAC Valves
9: 0-10 V Valves

1: 12-point Controller
2: 14-point Controller
3: Double Loop Controller

L: LonWorks Controller
B: Bacnet Controller

R: Configurable Controller
E: Programmable Controller

Product Warranty & Total Quality Commitment

All Distech Controls Product lines are built to meet rigorous quality standards and carry a two-year warranty. Distech Controls is an ISO 9001 registered company.

Specifications subject to change without notice.

Distech Controls, the Distech Controls logo and Open-to-Wireless, are trademarks of Distech Controls Inc. ; LonWorks is a registered trademark of Echelon Corporation Niagara^{AX}Framework is a registered trademark of Tridium, Inc. ; BACnet is a registered trademark of ASHRAE ; BTL is a registered trademark of the BACnet Manufacturers Association ; EnOcean is a registered trademark of EnOcean GmbH. All other trademarks are property of their respective owner.

